



MODÈLE	PLATE-FORME en MM	CAPACITÉ en KG	H. MAXI en MM	H. MINI en MM	LONGUEUR en MM hors tout	HAUTEUR en MM hors tout	POIDS en KG	BATTERIE	CHARGEUR
WP 80 inox	600 x 470	80	1450	130	795	1600	42	24V/7,2Ah	1,5A/230V
WP 85	600 x 470	85	1440	125	735	1600	39	24V/7,2Ah	1,5A/230V
WP 85 EM	600 x 470	80	1760	125	795	1920	42	24V/7,2Ah	1,5A/230V
WP 105	600 x 470	105	1345	130	845	1590	42	24V/7,2Ah	1,5A/230V
WP 105 EM	600 x 470	100	1655	130	845	1920	45	24V/7,2Ah	1,5A/230V
WP 105L	600 x 470	105	1345	105	850	1590	44	24V/7,2Ah	1,5A/230V
WP 105 L EM	600 x 470	100	1655	130	845	1920	45	24V/7,2Ah	1,5A/230V
WP 155	600 x 470	155	1345	130	850	1590	43	24V/7,2Ah	1,5A/230V
WP 155 EM	600 x 470	150	1655	130	850	1920	45	24V/7,2Ah	1,5A/230V
WP 155L	600 x 470	155	1345	105	850	1590	44	24V/7,2Ah	1,5A/230V
WP 155L EM	600 x 560	150	1345	105	850	1920	49	24V/7,2Ah	1,5A/230V
WP 205	600 x 560	205	1320	105	1015	1600	64	24V/7,2Ah	1,5A/230V
WP 250	600 x 560	250	1320	105	1040	1650	105	24V/7,2Ah	1,5A/230V